



PRODUCT DESCRIPTION FOR

Silt-Saver Fabric - BSRF PRIORITY 1

BSRF Priority 1 silt fence is a gray, continuous filament polyester, needlepunched, nonwoven fabric. BSRF Priority 1 conforms to the values in the following table:

FABRIC PROPERTY *		STANDARD VALUES
Fabric weight, oz/yd ²	ASTM 5261	4.8 (min. 4.0)
Thickness, mils	ASTM 5199	39.4 (29.0 – 53.1)
Grab Strength, lbs.	MD	130 (min. 108)
	CD	105 (min. 83)
Grab Elongation, %	MD	65 (min. 50)
	CD	80 (min. 50)
Trapezoid Tear, lbs.	MD	49 (min. 36)
	CD	45 (min. 31.5)
Mullen Burst, psi	ASTM 3786	190 (min. 160)
Puncture Strength, lbs.	ASTM 4833	49 (min. 36)
AOS	ASTM 4751	70 mesh (212 microns)

* Material sampled and tested in accordance to Quality Assurance test methods. Copies of these test methods and procedures are available upon request.

Silt-Saver, Inc. * 1200 Forrester Cemetery Rd, Covington Ga 30014
Phone 770-388-7818 * TOLL FREE 1-888-382-SILT (7458) * Fax 770-388-7640 * www.siltsaver.com

BNE/056160English Units

08/05/2014