

NONWOVEN MEDIUM-DUTY SILT FENCE

(BLACK BAND)

Designed for use in
Medium Duty Sensitive Areas



**100' PRE-STAKED ROLLS OAK /
HARDWOOD POSTS
SPACING AT 6' CENTERS**

Structural Integrity – Stormwater Release – Sediment Retention

- ▶ 36" tall, nonwoven spunbond polyester fabric
- ▶ The continuous black band at the top of the fence, as well as a unique method of attachment (sandwiching the fabric between the wood post and a bonding strip) enhances the strength of the system
- ▶ Belt provides strong linear support & disperses weight between posts
- ▶ Superior filtration in slurry conditions - Exceeds 96% filtration efficiency

BSRF Priority 2

P-2 Black Band - Part # P2

BSRF BB



Property (Typical)	Test Method	Values
Basis Weight	ASTM D3776	4.05 oz/yd ²
Thickness	ASTM D5199	35.8 mils
Tensile MD	ASTM D4632	133.0 lbf
Tensile CMD	ASTM D4632	97.0 lbf
Tear MD	ASTM D4533	56.0 lbf
Tear CMD	ASTM D4533	45.0 lbf
Elongation % MD	ASTM D4632	78%
Elongation % CMD	ASTM D4632	97%
Water Permeability	ASTM D4491	180 gpm/ft ²
Apparent Opening Size (AOS)	ASTM D4751	70 Sieve

Typical Values

Disclaimer: The information in this document relates to the specific material designated in this document and is not valid for such material used in combination with any other materials or in any process, unless otherwise approved by us in writing. Such information is to the best of our knowledge and belief accurate and reliable as of the date hereof, however no representation or warranty is made as to its accuracy, reliability, or completeness. It is a user's responsibility to verify itself as to the suitability of such information and the materials for their own particular use. We do not accept liability for any loss or damage that may occur from use of this information nor do we offer any

Silt Saver Inc. - 1200 Forrester Cemetery Rd.
Covington Ga 30014 ph. 770-388-7819